

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR
ELECTRICAL EQUIPMENT (IECEE) CB SCHEMESYSTEME CEI D'ACCEPTATION MUTUELLE DE CERTIFICATS
D'ESSAIS DES EQUIPEMENTS ELECTRIQUES (IECEE)
METHODE OC

CB TEST CERTIFICATE CERTIFICAT D'ESSAI OC

Product
Produit

CABLE MANAGEMENT- CABLE TRAY SYSTEMS

Name and address of the applicant
Nom et adresse du demandeurAISCAN, S.L.
CM CABESOLS, S/N
03410 BIAR (Alicante - España)Name and address of the manufacturer
Nom et adresse du fabricant

SAME AS ABOVE

Name and address of the factory
Nom et adresse de l'usine

SAME AS ABOVE

Note: When more than one factory, please report on page 2
Note: Lorsque il y plus d'une usine, veuillez utiliser la 2^{ème} page☐ Additional Information on page 2Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

See Annex

Trademark (if any)
Marque de fabrique (si elle existe)

AISCAN

Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeurModel / Type Ref.
Ref. De type

See references on the Annex

Additional information (if necessary may also be reported on
page 2)
Les informations complémentaires (si nécessaire,, peuvent être
indiqués sur la 2^{ème} page☒ Additional Information on page 2A sample of the product was tested and found
to be in conformity with
Un échantillon de ce produit a été essayé et a été
considéré conforme à la

IEC 61537:2006

As shown in the Test Report Ref. No. which forms part of this
Certificate
Comme indiqué dans le Rapport d'essais numéro de référence
qui constitue partie de ce CertificatCEL-0280/12-1/1-A1 up to CEL-0280/12-1/13-A1, CEL-0272/12-1/1-
A1 up to CEL-0272/12-1/16-A1This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme National de CertificationASOCIACIÓN ESPAÑOLA DE NORMALIZACIÓN Y CERTIFICACIÓN (AENOR)
CI Génova, 6
ES-28004 MADRID (SPAIN)

AENOR

Asociación Española de
Normalización y Certificación

Date: 2016-01-19

Signature: Avelino BRITO
Chief Executive Officer

ANNEX TO CB CERTIFICATE N° ES1690

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

PRODUCT: CABLE MANAGEMENT- CABLE TRAY SYSTEMS

Trade mark: AISCAN

Reference	Type of product	Width x Height (mm)	Safe working load (SWL) (N/m)	Impact resistance	Surface treatment	Type of accessory	Additional information
CMCG1010C	Tramo de bandeja/ Cable tray length (CMC)	100x100	1473 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1010/TCH9G100/D HTG1010/TDHTG100/TTU BCG10
CMCG1015C	Tramo de bandeja/ Cable tray length (CMC)	150x100	1143 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1015/TCH9G150/D HTG1015/TDHTG150/TTU BCG15
CMCG1020C	Tramo de bandeja/ Cable tray length (CMC)	200x100	1350 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1020/TCH9G200/D HTG1020/TDHTG200/TTU BCG20
CMCG1030C	Tramo de bandeja/ Cable tray length (CMC)	300x100	720 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1030/TCH9G300/D HTG1030/TDHTG300/TTU BCG30
CMCG1040C	Tramo de bandeja/ Cable tray length (CMC)	400x100	720 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1040/TCH9G400/D HTG1040/TDHTG400/TTU BCG40
CMCG1050C	Tramo de bandeja/ Cable tray length (CMC)	500x100	720 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1050/TCH9G500/D HTG1050/TDHTG500/TTU BCG50
CMCG1060C	Tramo de bandeja/ Cable tray length (CMC)	600x100	765 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1060/TCH9G600/D HTG1060/TDHTG600/TTU BCG60
CMCG10C	Tramo de bandeja/ Cable tray length (CMC)	100x35	990 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0310/TCH9G100/D HTG0310/TDHTG100/TTU BCG10
CMCG15C	Tramo de bandeja/ Cable tray length (CMC)	150x35	990 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0315/TCH9G150/D HTG0315/TDHTG150/TTU BCG15
CMCG320C	Tramo de bandeja/ Cable tray length (CMC)	200x35	990 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0320/TCH9G200/D HTG0320/TDHTG200/TTU BCG20

ANNEX TO CB CERTIFICATE N° ES1690

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Reference	Type of product	Width x Height (mm)	Safe working load (SWL) (N/m)	Impact resistance	Surface treatment	Type of accessory	Additional information
CMCG330C	Tramo de bandeja/ Cable tray length (CMC)	300x35	675 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0330/TC9G300/D HTG0330/TDHTG300/TU BCG30
CMCG610C	Tramo de bandeja/ Cable tray length (CMC)	100x60	1467 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0610/TC9G100/D HTG0610/TDHTG100/TU BCG10
CMCG615C	Tramo de bandeja/ Cable tray length (CMC)	150x60	1080 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0615/TC9G150/D HTG0615/TDHTG150/TU BCG15
CMCG620C	Tramo de bandeja/ Cable tray length (CMC)	200x60	1350 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0620/TC9G200/D HTG0620/TDHTG200/TU BCG20
CMCG630C	Tramo de bandeja/ Cable tray length (CMC)	300x60	635 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0630/TC9G300/D HTG0630/TDHTG300/TU BCG30
CMCG640C	Tramo de bandeja/ Cable tray length (CMC)	400x60	630 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0640/TC9G400/D HTG0640/TDHTG400/TU BCG40
CMCG650C	Tramo de bandeja/ Cable tray length (CMC)	500x60	855 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0650/TC9G500/D HTG0650/TDHTG500/TU BCG50
CMCG660C	Tramo de bandeja/ Cable tray length (CMC)	600x60	855 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0660/TC9G600/D HTG0660/TDHTG600/TU BCG60
CMCG810C	Tramo de bandeja/ Cable tray length (CMC)	100x80	1248 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0810/TC9G100/D HTG0810/TDHTG100/TU BCG10
CMCG815C	Tramo de bandeja/ Cable tray length (CMC)	150x80	1170 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0815/TC9G150/D HTG0815/TDHTG150/TU BCG15
CMCG820C	Tramo de bandeja/ Cable tray length (CMC)	200x80	1350 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0820/TC9G200/D HTG0820/TDHTG200/TU BCG20
CMCG830C	Tramo de bandeja/ Cable tray length (CMC)	300x80	647 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0830/TC9G300/D HTG0830/TDHTG300/TU BCG30
CMCG840C	Tramo de bandeja/ Cable tray length (CMC)	400x80	675 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0840/TC9G400/D HTG0840/TDHTG400/TU BCG40

ANNEX TO CB CERTIFICATE N° ES1690

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Reference	Type of product	Width x Height (mm)	Safe working load (SWL)	Impact resistance	Surface treatment	Type of accessory	Additional information
CMCG850C	Tramo de bandeja/ Cable tray length (CMC)	500x80	720 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0850/TC9G500/D HTG0850/TDHTG500/TTU BCG50
CMCG860C	Tramo de bandeja/ Cable tray length (CMC)	600x80	720 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0860/TC9G600/D HTG0860/TDHTG600/TTU BCG60
CMPG1010C	Tramo de bandeja/ Cable tray length (CMP)	100x100	1109 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1010/TC9G100/D HTG1010/TDHTG100/TTU BCG10
CMPG1015C	Tramo de bandeja/ Cable tray length (CMP)	150x100	990 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1015/TC9G150/D HTG1015/TDHTG150/TTU BCG15
CMPG1020C	Tramo de bandeja/ Cable tray length (CMP)	200x100	1179 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1020/TC9G200/D HTG1020/TDHTG200/TTU BCG20
CMPG1030C	Tramo de bandeja/ Cable tray length (CMP)	300x100	676 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1030/TC9G300/D HTG1030/TDHTG300/TTU BCG30
CMPG1040C	Tramo de bandeja/ Cable tray length (CMP)	400x100	639 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1040/TC9G400/D HTG1040/TDHTG400/TTU BCG40
CMPG1050C	Tramo de bandeja/ Cable tray length (CMP)	500x100	675 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1050/TC9G500/D HTG1050/TDHTG500/TTU BCG50
CMPG1060C	Tramo de bandeja/ Cable tray length (CMP)	600x100	612 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G1060/TC9G600/D HTG1060/TDHTG600/TTU BCG60
CMPG310C	Tramo de bandeja/ Cable tray length (CMP)	100x35	855 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0310/TC9G100/D HTG0310/TDHTG100/TTU BCG10
CMPG315C	Tramo de bandeja/ Cable tray length (CMP)	150x35	810 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0315/TC9G150/D HTG0315/TDHTG150/TTU BCG15
CMPG320C	Tramo de bandeja/ Cable tray length (CMP)	200x35	837 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0320/TC9G200/D HTG0320/TDHTG200/TTU BCG20

ANNEX TO CB CERTIFICATE N° ES1690

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Reference	Type of product	Width x Height (mm)	Safe working load (SWL)	Impact resistance	Surface treatment	Type of accessory	Additional information
CMPG330C	Tramo de bandeja/ Cable tray length (CMP)	300x35	630 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0330/TC9HG300/D HTG0330/TDHTG300/TTU BCG30
CMPG610C	Tramo de bandeja/ Cable tray length (CMP)	100x60	1080 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0610/TC9HG100/D HTG0610/TDHTG100/TTU BCG10
CMPG615C	Tramo de bandeja/ Cable tray length (CMP)	150x60	1080 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0615/TC9HG150/D HTG0615/TDHTG150/TTU BCG15
CMPG620C	Tramo de bandeja/ Cable tray length (CMP)	200x60	1080 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0620/TC9HG200/D HTG0620/TDHTG200/TTU BCG20
CMPG630C	Tramo de bandeja/ Cable tray length (CMP)	300x60	720 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0630/TC9HG300/D HTG0630/TDHTG300/TTU BCG30
CMPG640C	Tramo de bandeja/ Cable tray length (CMP)	400x60	720 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0640/TC9HG400/D HTG0640/TDHTG400/TTU BCG40
CMPG650C	Tramo de bandeja/ Cable tray length (CMP)	500x60	675 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0650/TC9HG500/D HTG0650/TDHTG500/TTU BCG50
CMPG660C	Tramo de bandeja/ Cable tray length (CMP)	600x60	675 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0660/TC9HG600/D HTG0660/TDHTG600/TTU BCG60
CMPG810C	Tramo de bandeja/ Cable tray length (CMP)	100x80	1035 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0810/TC9HG100/D HTG0810/TDHTG100/TTU BCG10
CMPG815C	Tramo de bandeja/ Cable tray length (CMP)	150x80	1035 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0815/TC9HG150/D HTG0815/TDHTG150/TTU BCG15
CMPG820C	Tramo de bandeja/ Cable tray length (CMP)	200x80	1215 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0820/TC9HG200/D HTG0820/TDHTG200/TTU BCG20
CMPG830C	Tramo de bandeja/ Cable tray length (CMP)	300x80	817 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0830/TC9HG300/D HTG0830/TDHTG300/TTU BCG30
CMPG840C	Tramo de bandeja/ Cable tray length (CMP)	400x80	765 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0840/TC9HG400/D HTG0840/TDHTG400/TTU BCG40

ANNEX TO CB CERTIFICATE N° ES1690

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Reference	Type of product	Width x Height (mm)	Safe working load (SWL)	Impact resistance	Surface treatment	Type of accessory	Additional information
CMPG850C	Tramo de bandeja/ Cable tray length (CMP)	500x80	765 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0850/TC9G500/D HTG0850/TDHTG500/TU BCG50
CMPG860C	Tramo de bandeja/ Cable tray length (CMP)	600x80	675 N/m	20 J	GALVANIZADO CALIENTE	Curva 90°/Tapa curva 90°/Derivación T/ Tapa Derivación T/Tapa recta	CH9G0860/TC9G600/D HTG0860/TDHTG600/TU BCG60

Clasificación:

- 6.1 According to material: **Metallic**
- 6.2 According to resistance to flame propagation: **Non flame propagation**
- 6.3 Electrical continuity: **With**
- 6.4 Electrical conductivity: **Non-conductive**
- 6.5 Resistance against corrosion: **Class 7**
- 6.6 According to temperature
 - Minimum temperature for transport, storage, installation and use: **-40 °C**
 - Maximum temperature for transport, storage, installation and use: **150 °C**
- 6.7 According to perforation in the base area: **Clasificación**
- 6.8 According to the free base area: **(No aplic)**
- 6.9 According to impact resistance: **up to 20 J**
- 10.2 SWL test (Safety Working Load)
 - Cable tray/span tested **1,5 m**

AENOR

Asociación Española de
Normalización y Certificación